

Application No. 10/669,033
Amendment dated February 10, 2006
Reply to Final Office Action of January 26, 2006

Docket No. CM06376J

Amendment to the Claims:

This listing of claims will replace all prior versions, and listing, of claims in the application.

Listing of Claims:

1. (currently amended): An audio accessory optimization system, comprising:
a radio having a controller; and
an audio accessory coupled to the radio, the audio accessory being controllerless, the audio accessory including an embedded memory coupled to the radio controller, the embedded memory containing audio optimization parameters to enable the radio to optimize the accessory audio performance, wherein the audio optimization parameters include at least one of: audio interface type, number of audio modes and signaling configuration, duplex capability, and receiver to transmitter transducer coupling parameters.
2. (original): The audio accessory optimization system of claim 1, wherein the radio is a portable radio.
3. (original): The audio accessory optimization system of claim 1, wherein the radio is a mobile radio.
4. (original): The audio accessory optimization system of claim 1, wherein the information contained in the embedded memory is organized in a hierarchical fashion.

Application No. 10/869,033
Amendment dated February 10, 2006
Reply to Final Office Action of January 26, 2006

Docket No. CM08376J

5. (original): The audio accessory optimization system of claim 1, wherein the information contained in the embedded memory is used to create an encrypted digital signature that is also stored in the embedded memory.

6. (original): The audio accessory optimization system of claim 1, wherein the embedded memory uses a single wire bus data communications means.

7. (original): The audio accessory optimization system of claim 6, wherein the single wire bus data communications means comprises a 1-Wire[®] bus.

Application No. 10/669,033
Amendment dated February 10, 2006
Reply to Final Office Action of January 26, 2006

Docket No. CM06376J

8. (currently amended): An audio accessory optimization system, comprising:
an audio accessory having content information stored therein, the audio accessory being controllerless, the content information for conveying information pertaining to the accessory's audio characteristics, the accessory for coupling to one of a plurality of radios wherein each of the plurality of radios includes a controller that detects the content information and optimizes the audio of the accessory in response thereto, wherein the content information includes at least one of: audio interface type, number of audio modes and signaling configuration, duplex capability, receive audio parameters, transmit audio parameters, and receiver to transmitter transducer coupling parameters.

9. cancelled

10. (currently amended): The audio accessory optimization system of claim 8 9, wherein the receive audio parameters include at least one of: power amplifier mode, line mode, transducer load impedance, maximum output level, effective sound pressure level (SPL), and conc envelope parameters.

11. cancelled.

Application No. 10/669,033
Amendment dated February 10, 2006
Reply to Final Office Action of January 26, 2006

Docket No. CM06376J

12. (previously presented): The audio accessory optimization system of claim 10, wherein the transmit audio parameters includes at least one of: minimum microphone bias voltage, maximum microphone bias voltage, microphone electrical model parameters, microphone sensitivity, and microphone acoustic model.

13. (original): The audio accessory optimization system of claim 12 wherein the microphone acoustic model includes at least one of: sensor type and response variation with distance.

14. cancelled

Application No. 10/669,033
Amendment dated February 10, 2006
Reply to Final Office Action of January 26, 2006

Docket No. CM06376J

15. (currently amended): An audio accessory, comprising
audio optimization parameters stored in the audio accessory, the audio accessory being
controllerless; and
the audio accessory for coupling to a variety of different radios, each radio having a controller and
each audio accessory having different audio characteristics, the audio accessory being automatically
adjusted by each radio controller based on the audio parameters stored in the audio accessory, wherein the
audio optimization parameters include at least one of: audio interface type, number of audio modes and
signaling configuration, duplex capability, and receiver to transmitter transducer coupling parameters.

16. (original): The audio accessory of claim 15, wherein the audio accessory includes a memory
device containing a plurality of descriptors that provide hierarchical information to enable radio
optimization of the audio accessory audio performance.